



AGM JUMP STARTER

PBI 2400HD ⚡ **12/24 V** ⚡ **2400/1200 CA**



+++

Rotomolded and unbreakable housing

Retractable handle and puncture-proof wheels

12 V accessory outlet
also used for memory saver mode

Anderson connectors for voltage
selection (12/24 V)

Heavy-duty curved clamps and
double-insulated, ultra-flexible 50mm² cable

Reverse polarity buzzer

Optional: Auxiliary connector for auxiliary cables

500 A fuse for short-circuit protection
and 1 spare fuse



THE PBI RANGE



PBI 1812

PBI 200

PBI 201

PBI 2400 HD

TECHNICAL INFORMATION

MODEL	PBI 1812	PBI 200	PBI 201	PBI 2400 HD
PART NUMBER	94065001C	94065200C	94065201C	232008
VOLTAGE (DC)	12V	12V	12/24V	12/24V
CRANKING AMPS (CA)	700	900	1800/900	2400/1200
CABLE LENGTH	0,71 m	1,59 m	1,70 m	1,52 m
CABLE CROSS SECTION	21 mm ²	21 mm ²	33 mm ²	50 mm ²
AUTOMATIC CHARGER	0,7 A	2 A	2 A	4 A



PACKAGING INFORMATION

MODEL	PBI 1812	PBI 200	PBI 201	PBI 2400 HD
NET WEIGHT	9,25 kg	11,75 kg	20,8 kg	30,5 kg
DIMENSIONS (L X W X H / MM)	330 x 170 x 363	360 x 150 x 440	425 x 230 x 455	475 x 290 x 550

HOW TO CHOOSE

PART NUMBER	MODEL	VOLTAGE	12 V								24V					
			<125*	150	175	250	300	350	500		100	250	500	1000	1500	2000
			HP* = CHECK YOUR ENGINE HP - LEGEND: ■ NORMAL ■■ INTENSIVE													
94065001C	PBI 1812	12V	■■	■	■											
94065200C	PBI 200	12V	■■	■■	■	■										
94065201C	PBI 201	12/24V	■■	■■	■■	■	■	■			■■	■■	■			
232008	PBI 2400 HD	12/24V	■■	■■	■■	■■	■■	■■	■		■■	■■	■■	■	■	

Related Battery charger Part number:

PBI 1812	PBI 200	PBI 201	PBI 2400 HD
EU: 94065021	EU: 2299003058CZ	EU: 2299003058CZ	EU: 865124-A
UK: 94065022	UK: 2299003058GZ	UK: 2299003058GZ	UK: 865124-A + 976158



Since
1947

Rue de la Baronnerie, 3
4920 Harzé - Belgium

info-be@schumacherelectric.com
www.schumachereurope.com

+32 4 388 20 17

@schumacherboosters